Pull Down Circular Saws

Metalworking Solutions Supplied



The Thomas range of circular sawing machines has been manufactured in Italy since 1957. High quality components and attention to design has resulted in a truly heavy duty machine, well able to withstand the intensive use of today's busy workshops. These machines are available with or without a pedestal base and are fitted with a two speed motor and a coolant pump as standard.

Machine Features

- Pull down design
- Anti-burr offcut clamp
- Mechanical coolant pump
- Mitres 45° left and right
- Quick lock vice
- 240V models available with single speed motor



Optional Equipment

- Pedestal base
- Roller track and measuring systems









TECHNICAL SPECIFICATIONS

MODEL STOCK CODE		Technics 250 15302		Super Cut 315 15303		350 Super Technics 15308	
Capacity		90°	45° L + R	90°	45° L + R	90°	45° L + R
0	mm	75	60	95	90	120	100
	mm	65	60	80	75	105	85
	mm	90 x 50	60 x 50	100 x 70	80 x 70	160 x 90	85 x 70
Blade Size	mm	250ø x	32 bore	315ø x 32 bore		350ø x 32 bore	
Blade Speed	rpm	40	/80	41/82		22/44/88	
Cutting Speed	m/min	31	/62	41/82		24/48/96	
Motor	Kw	0.75	- 0.95	1.3 - 1.9		1.3 - 1.7 - 2.4	
Length	mm	5	00	700		1100	
Width	mm	7	80	780		780	
Height	mm	1.	500	1530		1700	
Weight	Kg	1	15	148		186	
Operation Pull Down			Pull Down		Pull Down		
Vice	Manual		ınual	Manual		Manual	