



## H-Frame Press HFP

The HFP H frame press is ideal for a whole variety of bending, forming, pressing, straightening and a whole variety of operations. The hydraulic system is equipped with a manometer and a joystick lever to control the operation. A pair of V blocks are supplied as standard equipment.

The H-Frame press range is an economical alternative to a pressbrake, highly versatile and capable of a wide range of jobs and tasks.



### Machine Features

- Easily adjusted bed height with two hardened pins
- Bed designed to accept a variety of supports and jigs according to customer requirements
- Quiet hydraulic system
- Hydraulic cylinder mounted above providing vertical pressure
- Ideal for low or high volume operation.

### Optional Equipment

- Digital Read Out
- Limit Switch
- Hand Pump
- Foot Pedal Control (instead of joystick)
- Foot Pedal Control with Limit Switch (instead of joystick)



## TECHNICAL SPECIFICATIONS

MODEL	Stock Code	Power Tonnes	Distance between Frames mm	Stroke mm	Advance Speed mm/sec	Working Speed mm/sec	Return Speed mm/sec	Motor Power kW	Length mm	Width mm	Height mm	Weight kg
HFP 775/30	M4500	30	775	200	8	5	10	3	1500	700	1800	410
HFP 1040/60	M4501	60	1040	250	8	4	10	4	1850	700	2100	790
HFP 1070/100	M4502	100	1070	300	8	5	10	5.5	2050	1000	2200	1520
HFP 1570/100	M4503	100	1570	300	9	5	10	5.5	2500	1000	2200	1900
HFP 1070/150	M4504	150	1070	300	9	5	10	11	2050	1000	2270	1620
HFP 1570/150	M4505	150	1570	300	9	5	10	11	2500	1000	2270	2150