

BIANCO

Bianco SA DS MS Semi Automatic Bandsaws

Bianco have been manufacturing bandsaws in Italy for over thirty years and have built a reputation for producing precise, reliable, and accurate machines. All machines have modern cast bows from special alloys to ensure one of the highest precision bandsaw ranges available.

The Bianco SA DS MS Semi Automatic Single Mitre Bandsaws 415v are esteemed for their reliability, dependability and high accuracy which are hallmarks of Bianco Bandsaws.



Bianco
420 SA DS MS (Low Controller Position)

Machine Features


- Hydraulic cutting with variable pressure and variable speed (Semi-Automatic)
- Sliding Hydraulic vice
- Fast approach with auto bow height return setting
- Quick mitring swivel head up to 60°
- Cutting Angle Display (Digital Read Out)
- Cast bow construction
- Swarf brush
- Carbide blade guides for high accuracy
- 2 speed motor
- Heavy duty & fast cutting
- Coolant System
- Blade tension indicator
- Safety interlock switch fitted to band wheel cover
- Material length stop
- Low controller position

Optional Equipment

- High controller position
- Blade speed variation
- Spray mist cooling system
- Powered swarf brush
- Roller track and measuring systems



MECHANICAL BUNDLE CLAMPING DEVICE (OPTIONAL)



HYDRAULIC BUNDLE CLAMPING (OPTIONAL)



DRY COOLING DEVICE (OPTIONAL)



FREQUENCY CONVERTER (OPTIONAL WITH HIGH PANEL ONLY)



HIGH CONTROL PANEL (OPTIONAL)



ADJUSTABLE VICE PRESSURE (OPTIONAL)



BLADE DEFLECTION CONTROL DEVICE (OPTIONAL)



VARIABLE BLADE SPEED (10-100 M/MIN) (OPTIONAL WITH LOW PANEL ONLY)

WATCH THE MACHINE IN ACTION



TECHNICAL SPECIFICATIONS

MODEL	330SA DS MS				370SA DS MS				420SA DS MS				
STOCK CODE	15108								15123				
Capacity		90°	45°	60°	-45°	90°	45°	60°	-45°	90°	45°	60°	-45°
<input type="radio"/>	mm	260	150	120	130	280	230	140	200	280	260	170	200
<input type="checkbox"/>	mm	220	150	110	110	240	200	140	170	240	240	160	180
<input type="checkbox"/>	mm	330 x 120	190 x 150	120 x 120	190 x 100	350 x 140	230 x 230	140 x 140	220 x 100	420 x 200	260 x 200	160 x 160	250 x 100
Bed Height	mm	830				830				830			
Blade Size	mm	3010 x 27 x 0.9				3120 x 27 x 0.9				3270 x 27 x 0.9			
Cutting Speed	m/min	35 / 70				35 / 70				35 / 70			
Motor	Kw	0.9 - 1.5				0.9 - 1.5				0.9 - 1.5			
Length	mm	1500				1550				1600			
Width	mm	1600				1600				1600			
Height	mm	1700				1750				1800			
Weight	Kg	465				470				488			
Operation		Semi-automatic				Semi-automatic				Semi-automatic			
Vice		Hydraulic				Hydraulic				Hydraulic			