



### XR Compact Fibre Laser Cutting Machines



The Morgan Rushworth XR Compact is a range of compact fibre lasers equipped with a front-loading pull out table.

It's small footprint makes it perfect for tight workshops and restricted work spaces, while still allowing 1.5m x 1.5m cutting capacity.

Class leading components ensure superior cut quality, high reliability and reduced down time.

### Features and Benefits



**1.5m  
Bed Widths**



**1.5m  
Bed Lengths**




**Up to 3KW  
Laser Power**



**1.2G  
Acceleration**



**Lantek Expert  
Nesting  
Software**



**Optional  
Extraction &  
Filtration**

## Machine Features


- High performance IPG YLG Fibre Laser Source (1, 2 or 3kW)
- Fibre optic beam delivery system
- Automatic Focus Laser Cutting Head
- High strength, rigid gantry design to ensure high accuracy and allow high acceleration
- Yaskawa Servo Motors
- Wittenstein Rack & Pinion
- CNC 19" TFT Controller Screen
- Lantek Nesting Software
- Chiller
- Lens protective glass
- Parts / Scrap collector drawer
- Front Pull-Out Table
- Automatic Nozzle Cleaning and Calibration
- CE compliant complete machine enclosure

## Optional Equipment

- High Efficiency Extraction / Filtration System



**19" TFT CONTROLLER**



**SAFETY GLASS**



**AUTO FOCUS LASER CUTTING HEAD**

## TECHNICAL SPECIFICATIONS

| BED SIZE                                  |                      | XR 1515                     |
|---|----------------------|-----------------------------|
| Laser Source                              | kW                   | 1, 2 or 3kW                 |
| X Axis Travel                             | mm                   | 1524                        |
| Y Axis Travel                             | mm                   | 1524                        |
| Z Axis Travel                             | mm                   | 100                         |
| Rapid Traverse (X and Y Axis)             | m/min                | 90                          |
| Vector Speed                              | m/min                | 125                         |
| Acceleration                              |                      | 1.2G (15 m/s <sup>2</sup> ) |
| Maximum Sheet Size                        | mm                   | 1524 x 1524                 |
| Feed Rate                                 |                      | Programmable up to 90m/min  |
| Maximum table capacity                    | kg                   | 1000                        |
| Positioning accuracy                      | mm                   | ± 0.08                      |
| Repeatability                             | mm                   | ± 0.03                      |
| Automatic Nozzle Cleaning and Calibration |                      | Standard                    |
| Table                                     |                      | Front Pull-Out Table        |
| Fume Extractor                            | m <sup>3</sup> /hour | 2,500 (Optional)            |